

R-Temp[®] Fluid Advantages

Health and Environment:

- Non-toxic fluid.
- Low toxicity degradation products (tested by EPA and EPRI).
- Not listed by any federal or state agency as a hazardous waste.
- Tested non-mutagenic - classified non-carcinogenic.
- Does not persist in environment. Is biodegradable (silicone is not).
- No transportation restrictions.
- Easiest to dispose - simple to reprocess.

Performance and Safety:

- Superior dielectric properties - highest application to date: 115 kV, 550 kV BIL.
- Flawless field history - both electrical performance and fire safety.
- Arc Quenching Properties allow use in loadbreak devices.
- Greatest application versatility: pole type, pad type, unit substation, submersible, medium power transformers, modulators, voltage regulators, on-load tap changers, sectionalizing switches, commercial magnets, rectifiers, precipitators, etc.
- Excellent stability - no evidence of sludge or unusual property values in the oldest transformers sampled in the field performance study. Results exceed typical conventional transformer oil performance.
- Over 50 million liters in service.
- Greatest NEC[®] 450-23 compliance versatility using Factory Mutual Approval or exclusive expanded UL Classification.

BULLETIN 92008
FEATURE HIGHLIGHTS
April 1996 (supersedes 3/93)

COOPER POWER SYSTEMS
Dielectric Fluids Products
1900 East North Street
Waukesha, WI 53188-3899
800 643-4335; FAX 414 524-4654

 **COOPER** Power Systems